



## AGRICULTURE APOLLO



### APOLLO

**Colour:** green with cream helix.

**Temperature range:** - 10°C + 60°C / + 14°F + 140°F.

**Features:** Pvc hose reinforced with an anti-shock rigid Pvc spiral. Inside surface smooth, light corrugation outside. Strong and flexible, resistant to crushing, abrasion, atmospheric agents and most chemicals.

**Applications:** excellent for suction in general, particularly suitable to be used on slurry machines.

**Can be manufactured antistatic upon request**

## Technical Data

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Working Pressure	Bursting Pressure	Vacuum	Bending Radius	Roll Length	Volume
	mm	mm	mm	g/m	bar	bar	m H <sub>2</sub> O	mm	m	m <sup>3</sup>
AP 01 020.0 00C	20	3,1	3,5	300	7	21	10	100	50	0,070
AP 01 025.0 00C	25	3,3	3,7	390	6	18	10	125	50	0,094
AP 01 032.0 00C	31,8	3,9	4,3	580	6	18	10	160	50	0,142
AP 01 038.0 00C	38,1	3,8	4,4	670	5	15	10	190	50	0,190
AP 01 050.0 00C	50	4,2	4,8	960	4	12	10	250	50	0,310
AP 01 052.0 00C	50,8	4,2	4,8	970	4	12	10	250	50	0,314
AP 01 063.0 00C	63,5	4,7	5,3	1350	4	12	9	315	50	0,501
AP 01 076.0 00C	76,2	4,9	5,6	1630	3	9	9	380	50	0,646
AP 01 080.0 00C	80	5,0	5,9	1770	3	9	9	400	50	0,720
AP 01 100.0 00C	100	5,9	6,9	2590	3	9	8,5	500	30	0,768
AP 01 102.0 00C	102	5,9	6,9	2640	3	9	8,5	500	30	0,782
AP 01 127.0 00C	127	6,2	7,3	3450	2,5	7,5	8	630	30	1,228
AP 01 150.0 00C	151,5	6,7	7,9	4420	2	6	7	750	20	1,312
AP 01 152.0 00C	152,4	6,7	7,9	4410	2	6	7	750	20	1,319

Please contact us for other sizes