

VENTILATION, FUMES AND GASSES EOLO TERMORESISTENTE AS



EOLO TERMORESTENTE AS

Colour: black

Temperatura Range: -20°C+100°C

Features: flexible duct made of flame retardant PVC coated polyester fabric. Antistatic, it can be used in system where specific electrical features according to ATEX certification are required. Electrical resistance 10^7 Ohm/m according to ISO 8031

Applications: suction of air, fumes and gas where the neutralization of electrostatic charges is required.

Flame retardant, M2 grade according to NF P 92-503

Technical Data

| Part Number | Inside Ø | Weight | Bending radius | Roll lenght | Volume |
|-------------------|----------|--------|----------------|-------------|----------------|
| | mm | g/m | mm | m | m ³ |
| DS 01 040.0 000.0 | 40 | 205 | 20 | 10 | 0,074 |
| DS 01 051.0 000.0 | 51 | 255 | 26 | 10 | 0,092 |
| DS 01 060.0 000.0 | 60 | 300 | 30 | 10 | 0,119 |
| DS 01 063.0 000.0 | 63 | 315 | 32 | 10 | 0,138 |
| DS 01 065.0 000.0 | 65 | 325 | 33 | 10 | 0,142 |
| DS 01 070.0 000.0 | 70 | 450 | 35 | 10 | 0,163 |
| DS 01 076.0 000.0 | 76 | 485 | 38 | 10 | 0,192 |
| DS 01 080.0 000.0 | 80 | 510 | 40 | 10 | 0,240 |
| DS 01 090.0 000.0 | 90 | 575 | 45 | 10 | 0,291 |
| DS 01 102.0 000.0 | 102 | 640 | 51 | 10 | 0,285 |
| DS 01 110.0 000.0 | 110 | 685 | 55 | 10 | 0,317 |
| DS 01 115.0 000.0 | 115 | 720 | 58 | 10 | 0,353 |
| DS 01 120.0 000.0 | 120 | 750 | 60 | 10 | 0,380 |
| DS 01 127.0 000.0 | 127 | 790 | 64 | 10 | 0,414 |
| DS 01 130.0 000.0 | 130 | 810 | 65 | 10 | 0,465 |
| DS 01 140.0 000.0 | 140 | 870 | 70 | 10 | 0,499 |
| DS 01 152.0 000.0 | 152 | 945 | 76 | 10 | 0,626 |
| DS 01 160.0 000.0 | 160 | 925 | 80 | 10 | 0,739 |
| DS 01 163.0 000.0 | 163 | 945 | 82 | 10 | 0,758 |
| DS 01 180.0 000.0 | 180 | 1040 | 90 | 10 | 0,922 |
| DS 01 203.0 000.0 | 203 | 1170 | 102 | 10 | 0,951 |
| DS 01 228.0 000.0 | 228 | 1315 | 114 | 10 | 1,151 |
| DS 01 254.0 000.0 | 254 | 1585 | 127 | 10 | 1,348 |
| DS 01 279.0 000.0 | 279 | 1740 | 140 | 10 | 1,551 |
| DS 01 305.0 000.0 | 305 | 1900 | 153 | 10 | 1,816 |

| | | | | | |
|-------------------|-----|------|-----|----|-------|
| DS 01 315.0 000.0 | 315 | 1965 | 158 | 10 | 1,874 |
| DS 01 330.0 000.0 | 330 | 2060 | 165 | 10 | 1,961 |
| DS 01 356.0 000.0 | 356 | 2220 | 178 | 10 | 2,111 |
| DS 01 406.0 000.0 | 406 | 3110 | 203 | 10 | 2,412 |

