



## VENTILATION EOLO L

**Colour:** dark grey

**Temperature range:** -10°C +50°C

**Features:** plasticized PVC duct with antishock rigid PVC spiral. Perfectly smooth inside, outside corrugated. **More flexible and lighter than the Eolo it keeps unchanged the technical properties (wear, resistance and bending) thanks to the perfect balance between weight and mechanical resistance.** Resistant to atmospherical agents and to most chemicals.

### APPLICATIONS:

suction of air, fumes, gases, sawing, dust. Aerating and conditioning plants, woodworking plants etc. Resistant to low temperature.

### TECHNICAL DATA:

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Vacuum	Bending Radius	Roll Length	Volume
	mm	mm	mm	g/m	mH2O	mm	m	m <sup>3</sup>
EL 01 025.0 000.0	25	0,8	2,5	150	2,5	30	50	0,072
EL 01 030.0 000.0	30	0,8	2,6	190	2,5	35	50	0,102
EL 01 032.0 000.0	31,8	0,8	2,8	200	2	35	50	0,108
EL 01 035.0 000.0	35	0,8	2,9	225	2	35	50	0,137
EL 01 038.0 000.0	38,1	0,8	3,0	250	2	45	50	0,163
EL 01 040.0 000.0	40	0,8	3,0	270	2	50	50	0,178

EL 01 045.0 000.0	45	0,8	3,1	340	2	55	50	0,207
EL 01 050.0 000.0	50	0,8	3,5	415	2	60	50	0,263
EL 01 052.0 000.0	50,8	0,8	3,5	415	2	60	50	0,266
EL 01 060.0 000.0	60	0,8	3,6	485	1,6	70	50	0,361
EL 01 063.0 000.0	63,5	0,8	3,6	505	1,6	70	50	0,380
EL 01 070.0 000.0	70	0,9	3,8	560	1,5	90	50	0,541
EL 01 076.0 000.0	76,2	0,9	3,8	615	1,5	100	50	0,620
EL 01 080.0 000.0	80	0,9	4,3	725	1,5	110	50	0,655
EL 01 090.0 000.0	90	0,9	4,5	825	1,4	125	30	0,442
EL 01 100.0 000.0	100	0,9	4,6	940	1,3	140	30	0,642
EL 01 102.0 000.0	102	0,9	4,6	940	1,3	140	30	0,654
EL 01 110.0 000.0	110	1,0	5,0	1065	1,2	150	30	0,746
EL 01 120.0 000.0	120	1,0	5,0	1165	1	160	30	0,831
EL 01 127.0 000.0	127	1,0	5,0	1230	1	170	30	0,900
EL 01 130.0 000.0	130	1,0	5,0	1260	0,9	170	30	0,945
EL 01 140.0 000.0	140	1,0	5,1	1405	0,9	175	30	1,041
EL 01 150.0 000.0	151,5	1,1	5,2	1550	0,8	180	20	0,952
EL 01 152.0 000.0	152,4	1,1	5,3	1545	0,8	180	20	0,958
EL 01 160.0 000.0	160	1,1	6,0	1725	0,7	190	20	1,040
EL 01 180.0 000.0	180	1,1	6,0	1940	0,4	300	20	1,228
EL 01 200.0 000.0	200	1,1	6,0	2135	0,4	400	20	1,431
EL 01 203.0 000.0	203,2	1,1	6,0	2135	0,4	400	20	1,453
EL 01 250.0 000.0	250	1,2	6,8	3210	0,4	450	10	0,947
EL 01 300.0 000.0	300	1,2	6,9	3895	0,3	1000	10	1,450

Please contact our offices for not listed sizes

