



VENTILATION EOLO SE

Colour: blue

Temperature range: -25°C +50°C

Features: plasticized PVC duct with rigid antishock PVC spiral. Inside smooth, outside corrugated.

Flexible particularly at low temperatures, high mechanical resistance. It resists to atmospheric agents and to most chemicals

APPLICATIONS:

whereas a vacuum resistant flexible hose is needed, for industry, domestic vacuum cleaners, aerating and conditioning plants and suction of fumes, gasses, etc.

TECHNICAL DATA:

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Vacuum	Bending radius	Roll Length	Volume
	mm	mm	mm	g/m	m H2O	mm	m	m ³
EE 01 025.0 000.0	25	1,2	2,6	175	6	80	50	0,072
EE 01 032.0 000.0	31,8	1,4	3,1	280	6	110	50	0,110
EE 01 038.0 000.0	38,1	1,5	3,2	350	5	130	50	0,165
EE 01 040.0 000.0	40	1,5	3,2	370	5	140	50	0,180
EE 01 045.0 000.0	45*	1,6	3,4	450	5	160	50	0,210
EE 01 050.0 000.0	50	1,6	3,9	550	5	175	50	0,266

EE 01 052.0 000.0	50,8	1,6	3,9	560	5	175	50	0,270
EE 01 060.0 000.0	60*	2,0	4,6	850	5	200	50	0,372
EE 01 063.0 000.0	63,5	2,0	4,6	905	5	220	50	0,405
EE 01 076.0 000.0	76,2	2,0	5,2	1100	5	270	50	0,641
EE 01 080.0 000.0	80*	2,0	5,4	1200	5	290	50	0,672
EE 01 090.0 000.0	90*	2,0	5,4	1300	5	350	30	0,593
EE 01 102.0 000.0	102	2,1	5,6	1530	4,5	400	30	0,724
EE 01 127.0 000.0	127*	2,2	6,5	2200	4,5	500	30	0,996
EE 01 150.0 000.0	151,5*	2,5	7,3	3000	4	600	20	0,977
EE 01 200.0 000.0	200*	2,7	8,0	4100	3,5	800	20	1,577

*Available on request

Please contact our offices for not listed sizes

